

LED Linear Light / ECO Series



Applications: Factories, Shops, Parking Stores, Etc. ...

Features:

- Surface/Pendant Mounted
- Quick Wiring with easy openable cover,
- Anti-glare cover to make better light
- High Lumen efficiency,
- Long Life Time

Driver

Body
Alu.

CRI ≥ 80

IP20/44


IK04

°C
-20~+40

50,000H

Item No.	Power	Supply	Efficacy	CRI	Beam	CCT	Size
LLP14W3000ECO1	14W	220/240VAC	>100 Lm/W	80	120°	3000K	W25*H25*1000mm
LLP14W4000ECO1	14W	220/240VAC	>100 Lm/W	80	120°	4000K	W25*H25*1000mm
LLP14W6500ECO1	14W	220/240VAC	>100 Lm/W	80	120°	6500K	W25*H25*1000mm
LLP24W3000ECO1	24W	220/240VAC	>100 Lm/W	80	120°	3000K	W50*H70*1000mm
LLP24W4000ECO1	24W	220/240VAC	>100 Lm/W	80	120°	4000K	W50*H70*1000mm
LLP24W6500ECO1	24W	220/240VAC	>100 Lm/W	80	120°	6500K	W50*H70*1000mm

Light Distribution



Mech. Drawing

